

ATF CVT

Synthetic CVT Automatic Transmission Fluid

Description

Petrol Ofisi ATF CVT is a transmission fluid appropriate for belt or chain driven CVT type automatic transmissions.

Applications

They are used in the following applications:

- Chrysler Jeep NS-2
- Dodge CVTF+4
- Honda HCF2
- Hyundai SP-III
- Mini Cooper EZL799
- Mitsubishi SP-III
- Nissan NS-1
- Nissan NS-3
- Subaru iCVT
- Suzuki CVTF TC
- Toyota CVTF FE
- Daihatsu Ammix CVT
- GM Dex-CVT
- Honda HMMF *1)
- JASO 1A capable
- Mitsubishi CVTF-J1
- Nissan NS-2
- Subaru ECVT
- Suzuki CVT Green 1
- Suzuki NS-2
- Toyota CVTF TC

Benefits

- Enhanced friction organizing property and smooth driving comfort
- Reliable driving
- Extended equipment life
- Extended service intervals
- Enhanced gasket and oil seal compatibility

Performance

GM Dextron II, GM Allison C4, MB 236.1 Approval, MAN 339 Type VI, ZF TE ML-02F/03D/04D/14A/17C, Voith DIWA G607

Typical Specifications*

Density, @ 15 °C, kg/m ³	ASTM D 4052	0,844
Flash Point, COC, °C	ASTM D 92	230
Viscosity, 40 °C, mm ² /s	ASTM D 445	37
Viscosity, 100 °C, mm ² /s		7,66
Viscosity Index	ASTM D 2270	182
Pour Point, °C	ASTM D 97	-42

* Values shown may differ between productions.



Petrol Ofisi