

maximarine CYL SERIES

Description

MAXIMARINE CYL Series is a new generation cylinder lubricating oil that is produced with highly refined base oils and special additives, and meets the requirements of IMO 2020.

Applications

It is used to lubricate the cylinders of new generation two-stroke marine engines operating under heavy mechanical load and thermal conditions, and using low or high sulfur fuel.

Benefits

- It is designed for different needs and accommodates a wide range of applications.
- It keeps the wear on cylinders and liners under control.
- It prevents the formation of deposits and sediments in the pistons and rings.
- It provides a long service life at different ambient temperatures.

		MAXIMARINE CYL 25	MAXIMARINE CYL 40	MAXIMARINE CYL 55	MAXIMARINE CYL 70	MAXIMARINE CYL 100
SAE Viscosity Grade		50	50	50	50	50
Density, @ 15 °C, kg/m ³	ASTM D 4052	0,900	0,934	0,927	0,935	0,952
Flash Point COC, °C	ASTM D 92	272	282	276	276	272
Viscosity, 40 °C, mm ² /s	ASTM D 445	213	216	213,7	203	197
Viscosity, 100 °C, mm ² /s		19	19	19,9	19	19
Viscosity Index	ASTM D 2270	100	98	100	104	109
T.B.N., mgKOH/gr	ASTM D 2896	25	42	55,8	73	102
Pour Point, °C	ASTM D 97	-15	-22	-24	-27	-27

* Values shown may differ between productions.



Petrol Ofisi