

SUPERŞARJ SERIES

Monograde High Quality Diesel Engine Oils

Description

Monograde high viscosity index engine oil produced with high quality base oils and additives.

Applications

Can be used in heavy duty vehicles.

Benefits

- Thanks to a high level of TBN, protects the engine against rust, corrosion and wear when using high sulphur content fuel.
- Minimizes the deposit under severe conditions, prevents friction.
- Keeps fluidity at low temperatures due to its high viscosity index.
- Increases combustion efficiency by keeping the engine clean.

Performance

API CF/CF-4/SG, Allison C3, CAT T0-2, MIL-L-2104D

Typical Specifications*

SAE Viscosity Grade		10W	30	30(20TBN)	40	50
Density, 15 °C, kg/liter	ASTM D4052	0,886	0,890	0,902	0,900	0,899
Flash Point, COC, °C	ASTM D92	220	240	260	260	270
Viscosity, 40 °C, mm ² /s	ASTM D445	39,8	81	94	125	223
Viscosity, 100 °C, mm ² /s		6	9,80	11	13	19,50
Viscosity Index	ASTM D2270	107	100	102	98	99
Pour Point, °C	ASTM D97	-30	-18	-18	-15	-12

* Values shown may differ between productions.



Petrol Ofisi